

GreenFlow AC Charger (Coming Soon)

Single Phase (7kW) / Three Phase (11 / 22 kW) / Wall-mounted

User-friendly Experience

- ▶ Start/end Charging via an RFID Card or Smart Mobile App
- ▶ OTA Updates

Secure and Robust

- ▶ Suitable for Outdoor Environment
- ▶ Embedded RCD

Smart Charging

- ▶ Scheduled Pre-set Charging
- ▶ Compatible with Most EVs



MODEL	CAS7	CAT11	CAT22
Input Wiring	1P+N+PE	3P+N+PE	3P+N+PE
Rated Power	7 kW	11 kW	22 kW
Rated Input Voltage	230 Vac ±15%	380 Vac ±15%	380 Vac ±15%
Rated Current	32 A	16 A	32 A
Dimensions (W x H x D)	216 x 268 x 105 mm		
Material	PC + ASA		
Frequency	50 Hz ~ 60 Hz		
Color	White + Gray		
Cable Length	5 m		
Connector	Type 2		
Metering	On-Board Measurement		
LED	RGB LED		
RFID Card Reader	Mifare ISO / IEC14443 Type A		
Activation Method	Plug n' Play & RFID Card & App		
App Function	Remote start & stop, Scheduled Charging, Real-time Monitoring, Data Display, Power Adjusting		
Data Collector	Built-in Antenna		
Wi-Fi+Bluetooth	Standard		
RCD	6 mA DC + 30 mA Type A		
IP Rating	IP65		
IK Rating	IK10		
Certifications	CE (in progress) UKCA (planning)		
EMC	Class B		
IEC Standard	EN IEC 61851-1:2019 IEC61851-1:2017 IEC61851-21-2:2021		
Safety	Over-voltage protection, under-voltage protection, short circuit protection, grounding protection, over temperature protection, lightning protection		
Warranty	2 Years		
Temperature	-30°C ~+ 50°C		
Operating Humidity	5% ~ 95%		
Operating Altitude	< 2000 m		